



Distributed by:
 Safety Emporium
 PO Box 1003
 Blackwood, NJ 08012
 Ph: (866) 326-5412 toll-free
 Fax: (856) 553-6154
esupport@safetyemporium.com
www.safetyemporium.com



their safety is essential.

Products made to work hard—and built to last.

Type I Safety Cans

Protect workers and reduce fire risks when transferring, storing and dispensing flammable liquids

- Self-closing, leakproof lid protects vapors from escaping and guards against spills
- Positive-pressure relief cap automatically vents can to guard against rupture or explosion
- Stainless steel flame arrester prevents flashback ignition
- 100% leakproof construction with 10 year limited warranty
- Large label ID zone provides writing space to identify contents (on swinging-handle cans only)
- 24-gauge galvanized steel with tough, chemical-resistant powder-coat finish stands up to rigorous use
- Bottom lip provides grip to support pouring and resists accidental punctures when placed on uneven surfaces
- Extra capacity allows two-cycle engine oil or other additives
- FM approved; UL/ULC listed; accepted under CARB; meet OSHA and NFPA requirements



Color-Coded Safety Cans to differentiate liquids


Red = Gas, Yellow = Diesel
 Blue = Kerosene, Green = Oil



Optional 2-position polypropylene funnel aids in pouring and folds down for compact storage and filling.



Trigger release handle allows opening and dispensing with one hand.



Swinging handle is centered on the can to make carrying large cans easy.

Trigger Handle Type I Safety Cans

Capacity	Dimensions (OD x H)	Approvals / Compliance	Red Models	Yellow Models
1 pint (0.5 L)	4.812" x 6.75" (122 x 172 mm)	FM, UL/ULC, TÜV, CARB, OSHA, NFPA 30	10001	10011
1 quart (1 L)	4.812" x 8.25" (122 x 210 mm)		10101	10111
1 gallon (4 L)	7.25" x 11.5" (184 x 292 mm)	FM, UL/ULC, CARB, OSHA, NFPA 30	10301	—

Swinging Handle Type I Safety Cans

Capacity	Dimensions (OD x H)	Approvals / Compliance	Red Models	Yellow Models	Blue Models	Green Models
Type I Safety Cans						
1 gallon (4 L)	9.5" x 11" (241 x 279 mm)	FM, UL/ULC, TÜV, CARB, OSHA, NFPA 30	7110100	7110200	7110300	7110400
2 gallon (7.5 L)	9.5" x 13.75" (241 x 349 mm)		7120100	7120200	7120300	7120400
2.5 gallon (9.5 L)	11.75" x 11.5" (298 x 292 mm)		7125100	7125200	7125300	7125400
5 gallon (19 L)	11.75" x 16.875" (298 x 429 mm)		7150100	7150200	7150300	7150400
Type I Safety Cans with Funnel*						
1 gallon (4 L)	9.5" x 11" (241 x 279 mm)	FM, UL/ULC, TÜV, CARB, OSHA, NFPA 30	7110110	7110210	7110310	7110410
2 gallon (7.5 L)	9.5" x 13.75" (241 x 349 mm)		7120110	7120210	7120310	7120410
2.5 gallon (9.5 L)	11.75" x 11.5" (298 x 292 mm)		7125110	7125210	7125310	7125410
5 gallon (19 L)	11.75" x 16.875" (298 x 429 mm)		7150110	7150210	7150310	7150410

*Approvals apply to safety can only, not funnel.



11201Y



Funnels
 For 1 gallon (4 L) and
 larger safety cans

Description	Dimensions (OD x H)	Models
Polypropylene funnel	0.5" x 11.25" (13 x 286 mm)	11202Y
Bolt-on funnel with galvanized hose	1" x 14" (25 x 356 mm)	11089

(800) 798-9250 • Justrite.com

© 2021 Justrite Safety Group • Code JR460 (0721)