

Moisture Analyzers – Portfolio Overview

MB23

MB32

MB62

MB92

MB120

GOOD

BEST



Glass Heater Design

- Metal heater
- 50C – 160C (5C increments)
- 0.01g / 0.1% readability
- Backlit LCD display
- RS-232 Connectivity
- Standard Heating Profile
- Manual, Timed, Auto (A60)



Perfect for Routine Testing

- Carbon fiber heater
- 40C – 180C (1C increments)
- 0.001g / 0.01% readability
- 2-line LCD
- Menu navigation knob
- RS232, USB device
- Standard, Fast Heating Profiles
- Shut-Off – Manual, Timed, Auto (A30, A60, A90)
- Program Storage 2



Increased Versatility Expanded Applications

- Carbon fiber heater
- 40C – 200C (1C increments)
- 0.001g / 0.01% readability
- 2-line LCD
- Menu navigation knob
- RS232, USB device
- Standard, Fast, Ramp, Step Heating Profiles
- Shut-Off – Manual, Timed, Auto (A10, A30, A60, A90, A150)
- Program Storage 20
- Results Storage 100



Advanced Features Capacitive Touch Screen

- Carbon fiber heater
- 40C – 200C (1C increments)
- 0.001g / 0.01% readability
- Full Color Capacitive Touch Screen
- RS232, USB device, USB Host
- Standard, Fast, Ramp, Step Heating Profiles
- Shut-Off – Manual, Timed, Auto (A10, A30, A60, A90, A150, Custom)
- Program Storage 20
- Results Storage 200



Smart Guide Programming

- Halogen heating element
- 40C – 230C (1C increments)
- 0.001g / 0.01% readability
- Full Color Touch Screen
- RS232, USB Device, USB Host
- Standard, Fast, Ramp, Step Heating Profiles
- Shut-Off – Manual, Timed, Auto (A10, A30, A60, A90, A150, Custom)
- Program Storage 100
- Results Storage 1000
- Smart Guide

Distributed by:
 Safety Emporium
 PO Box 1003
 Blackwood, NJ 08012
 Ph: (866) 326-5412 toll-free
 Fax: (856) 553-6154
esupport@safetyemporium.com
www.safetyemporium.com